

# INSTALL INSTRUCTIONS

## C-KBM-TG3 TG3 KEYBOARD MOUNT PLATE

### C-QRS QUICK RELEASE SLIDE

### C-3065-3 TILT/SWIVEL ADAPTER

#### TOOLS REQUIRED:

Phillips screwdriver

#### HARDWARE:

QTY	DESCRIPTION	PART #
4	10-32 x 1/2" Phillips flat head machine screws	GSM33072
4	10-32 Keps nuts	GSM30028
3	#8 x 3/4" Phillips sheet metal screws	GSM33189

**Note: Order C-QRS Quick Release and C-3065-3 Tilt Swivel separately.**

#### Always!

- Read all instructions before installing any Havis, Inc. products.
- Check for obstructions (Wire, brake lines, fuel tank, etc.) before drilling any holes!
- Use hardware provided with install kit



Turn keyboard over to  
access screws



Remove (3) screws as  
shown.



Attach backing plate to  
keyboard using #8 x 3/4" sheet  
metal screws.



Tighten all screws



Line up C-QRS slide plate with nutserts in backing plate and attach using 8-32 x 1/2" Phillips flat head machine screws. *Discard 8-32 keps nuts that held assembly*



Attach slide guide bracket to C-3065-3 using (4) 10-32 x 1/2" Phillips machine screws and keps nuts. *Be sure to mount correct for proper tilt. (Shown mounted to C-SM-SA-1 Swing Arm Adapter for Stout Mount & Standard 9" Wide Consoles)*



Assembled slide guide bracket



Final assembly  
Turn over keyboard, pull to release knob and slide keyboard with plate onto assembled slide guide bracket.